

Industrial / Box Sealing Tape

149C Clear Transparent Carton Sealing Tape

Specifications:

- Application**
- Static free carton sealing electronics
 - Resistant to aging, weathering, UV light and yellowing
 - Provides excellent clarity, high shear strength to prevent “flagging”
 - Superior quick-stick performance , and controlled unwind to facilitate dispensing

Backing	Clear Cellophane film	
Adhesive	Solvent Natural Rubber	
Total Thickness	2 mil	
	Value	Test Method
Adhesion	34 oz/in	ASTM D-3330
Elongation	22% TD	ASTM D-882
Tensile Strength	28 lbs/in width	ASTM D-3759
Unwind Adhesion	13 oz/in 30 min conditioning	ASTM D-3330/D330M-04
Application Temperature	32°F to 150 °F	
Storage & Handling	Two years when stored at 70°F and 50% relative humidity Rolls must be transported and stored on protected surface	
Color	Clear	

Note:

All of the descriptive information, the typical performance data, and recommendations for the use for Polybond products shall be used only as a guide and do not reflect the specifications or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Polybond Corporation. All purchasers of Polybond Products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Polybond Corporation is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.