

## 2125 – Permanent, High Performance, Pressure Sensitive Adhesive

### Specifications:


<b>Application</b>	<ul style="list-style-type: none"><li>• Mounting packing slip envelopes</li><li>• Permanent labels</li><li>• Bag closure</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Good heat and low temperature resistance</li><li>• Easy to apply</li></ul>
<b>Adhesive</b>	Rubber
<b>Peel Adhesion</b>	8 lbs/in (180° Peel)
<b>F.D.A. Status</b>	Conforms to the composition requirements of Indirect Food Additive Regulation 21 CFR 175.105
<b>S.A.F.T.</b>	170°F (77°C)
<b>Color</b>	4 to 5 (Gardner Scale)
<b>Form</b>	1 lb mini pillow, 5 lb safe-melt, 55 gallon drum

#### Viscosity (CPS):

21000 @ 300°F (149°C)

8500 @ 325°F (163°C)

4500 @ 350°F (177°C)



#### Note:

All statements, technical information and recommendations concerning products sold or samples provided by Polybond Corporation are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold and samples of products provided with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. Polybond Corporation warrants the products to be free from defects in material and workmanship.