

## Industrial / Double-Sided Tape

# 2800 - Double-Sided Polyester Permanent Bag Sealing / Lift Edge

## Specifications:

<b>Application</b>	<ul style="list-style-type: none"><li>• Permanent Sealing</li><li>• Bag closure</li><li>• Seam Sealing</li><li>• Envelope Closure</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Security Seal</li><li>• Finger Lift Edge</li><li>• Heat knife Cuttable</li></ul>
<b>Backing</b>	Polyester - .5 Mil. Clear
<b>Adhesive</b>	Rubber – 2 Mil Liner & Exposed Side
<b>Release Liner</b>	White Polypropylene – 1.6 Mil. Available: Printed Red “Remove Liner To Expose Adhesive”
<b>Total Thickness</b>	4.5 Mil
<b>Adhesion</b>	150 oz/in width
<b>Sizes</b>	½” ¾” 1” x 3,000’ / Travers wound to 21,000’
<b>Maximum Temperature</b>	55°C • 155 °F
<b>Important</b>	Low Slip or No Slip Films are Highly recommended Corona Treatment on Film Surfaces Improves Adhesion Properties

### Note:

The above value represents average laboratory results. Each user should evaluate the tape to determine the suitability for each and every application and shall assume all risks and liability connection therewith