

## Industrial / Double-Sided Tape

# 2900M- Double-Sided Polyester Re-closable Bag Closure – Anti Static Poly Liner

## Specifications:

<b>Application</b>	<ul style="list-style-type: none"><li>• Temporary holding</li><li>• Bag closure</li><li>• Holding posters</li><li>• Core Starting</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Repositionable (low tack side)</li><li>• Easy peel off lift edge</li><li>• Removes cleanly</li></ul>
<b>Backing</b>	Polyester - .5 mil. clear
<b>Adhesive</b>	Synthetic Rubber
<b>Release Liner</b>	Metalized Polyester – 92 Gauge
<b>Total Thickness</b>	4.3 mil
<b>Adhesion</b>	15 oz/inch width liner side 100 oz/inch width exposed side
<b>Size</b>	½", ¾", 1" x 3,000' roll / 21,000' spool
<b>Maximum Temperature</b>	55°C • 155 °F
<b>Important</b>	Low Slip or No Slip Films are Highly recommended Corona Treatment on Film Surfaces Improves Adhesion Properties

### Note:

The above value represents average laboratory results. Each user should evaluate the tape to determine the suitability for each and every application and shall assume all risks and liability connection therewith

