

Industrial / Adhesive Transfer Tape

4115-TT - Permanent Unsupported – Printed Paper Liner

Specifications:

Application	<ul style="list-style-type: none">• Tyvek envelope closure• Tyvek wristband sealing• Secure retail fold-over tab• Medium weight box closure
Benefits	<ul style="list-style-type: none">• High peel strength• Excellent shear and holding power• Easy peel extended liner• Wide range service temperature
Backing	None
Adhesive	Permanent Rubber – 1.5 Mil.
Release Liner	Printed Paper – 2.5 Mil. “Remove Liner To Expose Adhesive”
Total Thickness	4.0 Mil.
Adhesion	125 oz. in/width
Standard Sizes	¾”, 1”, 1.25”, 1.5” x 3000’ (custom sizes available)
Maximum Temperature	93°C • 200 °F
Important	Adhesives Are Compliant With FDA Regulations For Indirect Food Contact – CFR 175.105

Note:

All statements, technical information and recommendations concerning products sold or samples provided by Polybond Corporation are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold and samples of products provided with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. Polybond Corporation warrants the products to be free from defects in material and workmanship