

## Industrial / Double-Faced Tape

# 4425 - Double-Faced Film Supported – High Tack – Synthetic Rubber Adhesive

## Specifications:

<b>Application</b>	<ul style="list-style-type: none"><li>• Mounting Posters</li><li>• POP display seaming</li><li>• Hang tag fold overs</li><li>• Core start up</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Excellent quick stick</li><li>• High shear and holding strength</li><li>• Easy peel extended liner</li><li>• Printed instructional print</li></ul>
<b>Backing</b>	Polyester
<b>Adhesive</b>	Exposed: Permanent Rubber – 1.5 mil. Liner Side: Permanent Rubber – 2.0 mil.
<b>Release Liner</b>	Printed Paper – 2.5 mil. “Remove Liner To Expose Adhesive”
<b>Total Thickness</b>	4 Mil.
<b>Adhesion</b>	150 oz. in/width
<b>Extension Width</b>	1/8” in each side
<b>Standard Sizes</b>	¾”, 1”, 1.25”, 1.5”, 2” x 1620’ (custom sizes available)
<b>Maximum Temperature</b>	93°C • 200 °F
<b>Important</b>	Adhesives Are Compliant With FDA Regulations For Indirect Food Contact – CFR 175.105

### Note:

All statements, technical information and recommendations concerning products sold or samples provided by Polybond Corporation are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold and samples of products provided with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. Polybond Corporation warrants the products to be free from defects in material and workmanship