

Industrial / Double-Sided Tape

4560W - Double-Sided Acrylic UPVC Tape

Specifications

- Application**
- Permanent bonding to most substrates, such as metal wood glass cement and plastics.
 - For mounting decorative trims such as PVC profile for the furniture industry.
 - Fastening of nameplates, trophy, luggage tag, wooden trims, signs, etc.

- Benefits**
- Excellent resistance to UV and aging.
 - Good shear resistance at normal and elevated temperature.
 - Good tack, high adhesive mass.
 - Acrylic adhesive system.

Backing	UPVC
Adhesive	Solvent Acrylic
Liner	Silicone paper – Mustard Color
Total Thickness	8.5 mil
Adhesion	88 oz/in
Tensile Strength	MD:15.40 lbs/in (7.0 kg/mm ²); TD: 9.9 lbs/in (4.5 kg/mm ²)
Temperature	-30 °C to 90 °C • -22 °F to 194 °F
Color	White

Note:

All statements, technical information and recommendations concerning products sold or samples provided by Polybond Corporation are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold and samples of products provided with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. Polybond Corporation warrants the products to be free from defects in material and workmanship