

## Industrial / Double-Sided Tape

### 4832B - Double Coated Black Closed Cell Polyethylene Foam Tape (1/32")

#### Specifications

<b>Application</b>	<ul style="list-style-type: none"><li>• Mounting and joining</li><li>• Window Glazing</li><li>• Sound/Vibration dampening</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Temperature, UV and plasticizer resistant</li><li>• Quick stick, high shear</li><li>• Conformability and compressibility</li></ul>
<b>Backing</b>	Closed cell polyethylene foam
<b>Adhesive</b>	Rubber Based Adhesive
<b>Liner</b>	4 Mil. Blue Poly
<b>Total Thickness</b>	0.079 mm • 31 mil
<b>Adhesion</b>	100 oz/in (PSTC-101)
<b>Tack</b>	750 (oz/in) (ASTM-D2979)
<b>Application Temperature</b>	18 to 45 (°C) • 65 to 125 (°F)
<b>Tensile Strength</b>	30 (lbs./in) (PSTC-131)
<b>Color</b>	Black

**Note:**

The above value represents average laboratory results. Each user should evaluate the tape to determine the suitability for each and every application and shall assume all risks and liability connection therewith.