

## Industrial / Double-Sided Tape

### 5120R - Double-Sided Polyester

#### Specifications:

<b>Application</b>	<ul style="list-style-type: none"><li>• Mounting point of purchase displays</li><li>• Mounting shelving materials</li><li>• Holding posters and retail signs</li><li>• Loyalty price change tag backing</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Clean removability from Paint, metal, glass, and aluminum</li><li>• Excellent cold temperature performance</li><li>• True dry edge easy removal liner</li><li>• Extra long length rolls</li></ul>
<b>Carrier</b>	0.5 mil. Polyester
<b>Liner Adhesive</b>	1 mil. Synthetic Rubber
<b>Unwind Adhesive</b>	1.3 mil. Synthetic Rubber
<b>Liner</b>	3.2 mil. Paper Printed "Remove Liner To Expose Adhesive"
<b>Total Thickness</b>	5.8 mil.
<b>Adhesion SS</b>	Exposed Side: 120 oz/in Liner Side: 90 oz/in
<b>Loop Tack SS</b>	80 oz.
<b>Color</b>	Light Amber
<b>Standard Sizes</b>	¾" and 7/8" x 1800'/2500'/3,000'/3500'/4500'
<b>Surface Preparation</b>	Surface tape is applied must be clean, dry and free of grease or oil.

**Note:**

All statements, technical information and recommendations concerning products sold or samples provided by Polybond Corporation are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold and samples of products provided with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. Polybond Corporation warrants the products to be free from defects in material and workmanship.