

## Industrial / Box Sealing Tape

# 526C Clear BOPP Carton Sealing Tape

## Specifications:

### Features

- All-temperature box sealing performance
- Resistant to aging, weathering, UV light and yellowing
- Provides excellent clarity, high shear strength to prevent “flagging”
- Superior quick-stick performance , and controlled unwind to facilitate dispensing

**Backing** 1.6 mil Clear BOPP film

**Adhesive** 1.0 mil Emulsion Acrylic

**Total Thickness** 2.6 mil

|                         | <b>Value</b>                 | <b>Test Method</b>   |
|-------------------------|------------------------------|----------------------|
| <b>Adhesion</b>         | 22 oz/in                     | ASTM D-3330          |
| <b>Elongation</b>       | 130% TD                      | ASTM D-882           |
| <b>Tensile Strength</b> | 28 lbs/in width              | ASTM D-3759          |
| <b>Unwind Adhesion</b>  | 13 oz/in 30 min conditioning | ASTM D-3330/D330M-04 |

**Application Temperature** 32°F to 150 °F

**Roll Tolerances** Length: +/- 5%  
Width: +/- 0.0625 in (1/16 in)

**Storage & Handling** Two years when stored at 70°F and 50% relative humidity  
Rolls must be transported and stored on protected surface

**Color** Clear

### Note:

All of the descriptive information, the typical performance data, and recommendations for the use for Polybond products shall be used only as a guide and do not reflect the specifications or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Polybond Corporation. All purchasers of Polybond Products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Polybond Corporation is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.