

Industrial / Double-Sided Tape

5628 Double-Sided Polyester

Permanent - Removable Adhesive Tape

Specifications:

Application	<ul style="list-style-type: none">• Removable vinyl sign graphics• Temporary labels and decals• Holding posters and signage• Core Starting
Benefits	<ul style="list-style-type: none">• Repositionable (Low tack side)• Removes cleanly (Low tack side)• No adhesive residue• Aggressive tack exposed side
Backing	0.50 mil. Clear Polyester
Adhesive	Solvent Acrylic
Liner	60# (3.5 Mil. White Bleached Kraft Paper)
Total Thickness	4.0 mil. (exclusive of liner)
Adhesion	Exposed Side: 90 oz./in Liner Side: 28 oz./in
Elongation	130 % MD (ASTM-D-882)
Tensile Strength	1800 MD Kg/cm (ASTM-D-882)
Available	54" Master – Slit to width - Spools
Maximum	
Temperature	107°C • 225°F
Color	Amber

All of the descriptive information, the typical performance data, and recommendations for the use for Polybond products shall be used only as a guide and do not reflect the specifications or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Polybond Corporation. All purchasers of Polybond Products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Polybond Corporation is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.