

Industrial / Double-Sided Tape

6700M - Double-Sided Polyester Permanent Bag Closure / Anti-Static Liner

Specifications:

Application	<ul style="list-style-type: none">• Permanent Bag closure• Permanent seaming tape• Protective pouch closure• Document pouch closure
Benefits	<ul style="list-style-type: none">• Immediate bond when sealed• Easy Peel True Dry Edge• Hot Knife Cuttable
Backing	Polyester - .5 Mil. Clear
Adhesive	Permanent Rubber
Release Liner	Metalized PET – 1 Mil.
Total Thickness	4.1 Mil.
Adhesion	100 oz. in/width
Size	½", ¾", 1" x 3,000' / 21,000' spool
Maximum Temperature	55°C • 155 °F
Important	Low Slip or No Slip Films are Highly recommended Corona Treatment on Film Surfaces Improves Adhesion Properties

Note:

All of the descriptive information, the typical performance data, and recommendations for the use for Polybond products shall be used only as a guide and do not reflect the specifications or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Polybond Corporation. All purchasers of Polybond Products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Polybond Corporation is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.